



Noren Products Inc. 1010 O'Brien Drive, Menlo Park, CA 94025
 (650) 322-9500, FAX (650) 324-1348
 In Business Since 1968

Specifications & Dimensions, Metric

Cabinet Style	Rack U Space 4.5 cm	Heat Removal (Watts) ^{1,2}	Reduces Noise By	Noise Reduction in Decibels ΔdBA	Example dBA @ 1 Meter with Front Door		Outside Dimensions (cm) ^{3,4}			Inside Dimensions (cm) ³			Rack Dimensions (cm) ³	Total Cabinet Weight		
					Open	Closed	H	W	D	H	W	D			H	W
ACL16TD	16u	1600	>99%	38	71	33	150	61	104	74	51	94	71	48	79	143 kg
ACL24TD	24u	1600	>99%	38	71	33	185	61	104	112	51	94	107	48	79	159 kg
gCab	N/A	800	>99%	32	67	35	81	66	66	61	30	56	---	N/A	---	63 kg
oCab	12u	2000	>88%	16	61	45	74	61	104	53	51	91	53	48	79	54 kg
oCab Plus 3	15u	2200	>88%	16	61	45	89	61	104	71	51	91	69	48	79	62 kg
oCab Short	12u	1200	>88%	16	61	45	74	61	76	53	51	61	53	48	46	35 kg
rCab	5u	900	>99%	32	67	35	76	71	66	30	48	56	18	48	46	68 kg
vCab	16u	1600	>99%	38	71	33	150	61	104	74	51	94	74	48	79	149 kg
xCab	6u	1200	>99%	38	71	33	76	61	104	30	51	94	28	48	79	93 kg
ACL14SF ⁽⁵⁾	14u	1400	>99%	32	67	35	112	61	104	66	51	61	64	48	46	132 kg
ACL24SF ⁽⁵⁾	24u	1400	>99%	32	67	35	160	61	104	107	51	61	107	48	46	177 kg
ACL PC ⁽⁵⁾	N/A	260	>99%	32	67	35	86	46	76	64	33	64	---	N/A	---	68 kg

Notes:

1. The Heat Removal in Watts is the waste heat from your electronic gear that would otherwise accumulate inside your cabinet.
2. Heat Removal shown will give a slight internal cabinet temperature rise of 6-9°C above ambient room temperature in most cases. For more detailed information visit our web site at <http://www.acoustilock.com/FAQ.html>
3. All cabinet dimensions may vary plus or minus 1 centimeter.
4. All outside cabinet heights include 10 cm casters - fully rotating and locking.
5. Availability limited to existing inventory for Models: ACL14SF, ACL24SF, and ACL PC.